HuBei Petrokh Petroleum Machinery Co., Ltd.

Oil & Gas Petroleum Machinery — Fracturing · Cementing · Acidizing · Workover

Web: https://www.petrokh.net | Email: chinapetroleummachinery@hotmail.com | Jingzhou, Hubei, China

GJC40-17 Cementing Truck

Truck-Mounted Well Cementing Unit

The GJC40-17 well cementing truck is equipped with a horizontal triplex single-function plunger pump, slurry mixing, hydraulic, pneumatic and mechanical transmission systems. Rated at 40 MPa and 1700 L/min from its 300 plunger pump, it serves deep, medium and shallow well cementing.

Technical Specifications

Plunger Pump	300 horizontal triplex single-function
Chassis	Beiben 6×4 / 6×6 / Shacman 6×4
Deck Engine	Cummins KT19-C450 / DDC S60
Deck Gearbox	BY400 / Allison OFS4700
Maximum Pressure	40 MPa
Maximum Displacement	1700 L/min
Injection Centrifugal Pump	4×3 / 2×3 (optional)
Priming Centrifugal Pump	RA 6×5 / PN 6×5 (optional)
Water-Supply Centrifugal Pump	4×3 / 2×3 (optional)
Max. Well Depth	up to 4500 m
Weight	22000 kg
Overall Dimension	≈10250 × 2500 × 3850 mm

Typical Applications

- Deep, medium and shallow oilfield cementing
- Cement slurry mixing and displacement
- Well service auxiliary pumping

Certification & Testing: API · HSE · ISO 9001:2008 Certified Manufacturer | Established in 2006. This unit is designed and built for oilfield service duty; full factory test reports and configuration data are available on request.